

# TECH LINE Coatings

## SAFETY DATA SHEET

### Section 1 – Identification

**Product Identifier:** Grey Ice

**Part Number:** GHK

**Recommended Use:** Exhaust and High Temperature Coating

**Restrictions on Use:**

**Manufacturer / Supplier:**

Tech Line Coatings, Inc  
26844 ADAMS AVE.  
MURRIETA, CA 92562  
USA  
Phone/Fax 1-865-773-0597  
www.techlinecoatings.com

For Industrial Use Only  
Keep out of reach of children.  
Not recommended for use on Medical equipment.  
Not recommended for use on Aviation equipment.

**Emergency Phone:** N. America +1-800-535-5053  
Intl. +1-352-323-3500

### Section 2 – Hazards Identification

**Signal Word:** Danger

**Symbols:**



#### Hazard Statements:

Flammable liquid and vapor  
Harmful in contact with skin  
Harmful if inhaled  
Causes skin Irritation  
Causes Eye Irritation  
Suspected of causing genetic defects  
Suspected of causing cancer  
Suspected of damaging fertility or the unborn child  
May cause damage to organs; brain, liver, kidney, bladder, central nervous system  
Harmful if swallowed

#### GHS Classification:

GHS Classification:	Category
Flammable Liquid	3
Acute Toxicity Dermal	4
Acute Toxicity Inhalation	4
Skin Irritation	2
Eye Irritation	3
Germ Cell Mutagenicity	2
Carcinogenicity	2B
Toxic to Reproduction	2
Specific Target Organ Toxicity Single Exposure	2

#### Precautionary Statements:

Keep away from heat / sparks / open flames / hot surfaces. - No Smoking. Ground / bond container and receiving equipment. Use explosion proof electrical / ventilating / lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

In case of fire use alcohol-resistant foam, dry chemical or carbon dioxide

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

Wear protective gloves / protective clothing (chemical proof). Wear eye protection and face protection. Wash hands, face and any exposed skin thoroughly after handling. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not eat drink or smoke when using this product. Do not breath fumes / mist / vapors / spray. Use only outdoors or in a well ventilated area.

If swallowed: immediately call a poison center / doctor for medical advice. Do NOT induce vomiting.

If on skin: wash with plenty of water. Call a poison center / doctor if you feel unwell or if irritation occurs. Immediately take off all contaminated clothing and wash it before reuse.

If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center / doctor for medical advice.

If in eyes: Rinse cautiously in water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison control center / doctor.

If exposed or concerned: Get medical advise / attention, from a poison center / doctor.

Dispose of Contents / container in accordance with regulations in your area. See section 13 for additional information.

### **Section 3 – Composition / Information On Ingredients**

<b>Component Name</b>	<b>Common Name / Synonyms</b>	<b>CAS#</b>	<b>% of Weight</b>
Xylene		1330-20-7	< 32%
Molybdenum disulfide	MoS2	1317-33-5	< 4%
Isobutyl Alcohol	Isobutanol	78-83-1	< 14%
Toluene		108-88-3	< 12%
Pigment Black 33	Iron Manganese Oxide	75864-23-2	< 3%
Ethyl benzene		100-41-4	< 6%

Other ingredients are not hazardous based on OSHA standard Section 29 CFR 1910.1200

### **Section 4 – First Aid Measures**

#### **General Advice**

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

#### **If inhaled**

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

#### **In case of skin contact**

Wash off with soap and plenty of water, and remove contaminated clothing shoes and leather goods. Consult a physician..

#### **In case of eye contact**

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

#### **If swallowed**

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

### **Section 5 – Fire Fighting Measures**

<b>Extinguishing Media:</b> Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.	<b>Special Fire Fighting Procedures:</b> Wear self contained breathing apparatus for fire fighting if necessary.
<b>Unusual Fire And Explosion Hazards:</b> Hazardous decomposition products formed under extreme fire conditions. - Carbon and other oxides. Vapors are heavier than air and may travel to a source of ignition and flash back.	<b>Additional Information:</b> Use water spray to cool unopened containers.

### **Section 6 – Accidental Release Measures**

#### **Methods for Containment and Clean Up**

- Soak up with inert absorbent material.
- Keep in suitable, marked and closed containers for disposal.
- Use spark-proof tools and explosion-proof equipment.
- Remove sources of ignition.
- Warn other workers of spill.
- Wear protective equipment

- NIOSH Approved Respirator
- Gloves
- Safety Glasses
- Do not allow material to be released into the environment.

**Additional Information:**

- See Section 7 for safe handling information.
- See Section 8 for PPE information
- See Section 13 for disposal information

**Section 7 – Handling And Storage**

**Handling:**

Do not breathe vapors or mists from spraying. Avoid contact with skin and eyes. Use with adequate ventilation to maintain exposure levels below established exposure limits. Wear personal protective equipment. If required wear an appropriate NIOSH approved respirator with paint prefilter. Use explosion-proof equipment. Do not get in eyes, on skin, or on clothing. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. Take precautionary measures against static discharges.

**Storage:**

Store in area suitable for flammable liquids. Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat and sources of ignition.

**Section 8 – Exposure Controls And Personal Protection**

Component	ACGIH TLV	OSHA PEL	NIOSH REL
Xylene	TLV: 100 ppm TWA: 150 ppm	TWA: 100 ppm	100 ppm 10 hour shift 200 ppm 10 minutes
Molybdenum disulfide	TWA 10 mg/m <sup>3</sup>	TWA 10 mg/m <sup>3</sup>	No data available
Isobutyl Alcohol	TWA: 50 ppm	TWA: 50 ppm	TWA: 50 ppm
Toluene	TWA: 50 ppm	TWA: 300 ppm	STEL: 150 ppm TWA: 100 ppm
Pigment Black 33	TWA 0.2 mg/m <sup>3</sup> as Mn	CLV 5 mg/m <sup>3</sup> as Mn	No data available
Ethyl benzene	TLV: 100 ppm TWA: 125 ppm	TWA: 100 ppm	TWA: 100 ppm

**Engineering Controls:**

Exhaust ventilation.  
Showers  
Eyewash stations  
Use in a well-ventilated area.

**Respiratory Protection:**

Use NIOSH approved respirator if TWA/TLV limits are exceeded

**Protective Gloves:**

CHEMICAL RESISTANT

**Eye Protection:**

SAFETY GLASSES WITH SIDE SHIELDS OR GOGGLES

**Other Protective Equipment:**

WEAR PROTECTIVE CLOTHING, CHEMICAL RESISTANT OR OTHER PROTECTIVE OUTERWEAR, AVOID CONTACT WITH SKIN OR EYES

**Ventilation:**

Local Exhaust: Use To Maintain Below TWA Limits

**Mechanical:**

Use Non-Sparking Equipment

**Work / Hygienic Practices:**

wash thoroughly after handling product and before eating, drinking or smoking

**Section 9 – Physical And Chemical Properties**

Form : liquid  
Color : Dark Grey / Black  
Odor : Mixture of Solvents

Odor Threshold:	Not Established
pH :	No data available
Melting point/range :	No data available
Initial boiling point :	> 150° F.
Flash point :	> 94° F.
Evaporation Rate:	No data available on mixture
Upper/lower flammability or explosive limits:	No data available on mixture
Vapor pressure	No data available on mixture
Vapor density	> 1 - (air =1)
Relative density	No data available on mixture
Solubility(ies)	No data available on mixture
Partition coefficient: n-octanol/water	No data available on mixture
Auto-ignition temperature	No data available on mixture
Decomposition temperature	No data available on mixture
Viscosity	Not Established
Total VOC	< 610 g/l

### **Section 10 – Stability And Reactivity**

---

<b>Stability:</b>	STABLE
<b>Possibility of hazardous reactions:</b>	Hazardous Polymerization: Will not occur.
<b>Conditions to avoid:</b>	Avoid storage of open containers at elevated temperatures. Heat, flames and sparks, direct sunlight.
<b>Incompatible Materials:</b>	Oxidizing material can cause a reaction.
<b>Hazardous Decomposition Products:</b>	Thermal breakdown of this product during fire or very high heat conditions may evolve the following decomposition products: Silicon dioxide. Carbon oxides. Metal oxides. Formaldehyde.

### **Section 11 – Toxicological Information**

---

#### **Potential Health Effects**

<b>Inhalation</b>	Toxic if inhaled.
<b>Ingestion</b>	Toxic if swallowed
<b>Skin</b>	Harmful in contact with skin. Causes skin irritation.
<b>Eyes</b>	Causes Serious Eye Damage

#### **Acute Toxicity**

Xylene	Oral LD50	mouse: LD50 = 2119 mg/kg rat: LD50 = 4300 mg/kg
	Inhalation LC50	rat: LC50 = 5000 ppm/4H
	Dermal LD50	rabbit: LD50 = >1700 mg/kg
Molybdenum disulfide	Oral LD50	No data available

	Inhalation LC50	LC50 Inhalation - rat - 4 h - > 2,820 mg/m3 Remarks: Lungs, Thorax, or Respiration:Other changes.
	Dermal LD50	No data available
Isobutyl Alcohol	Oral LD50	LD50 Oral - rat - 2,460 mg/kg LD50 Oral - rat - 2,500 - 6,400 mg/kg
	Inhalation LC50	LC50 Inhalation - rat - 4 h - 8000 ppm
	Dermal LD50	LD50 Dermal - rabbit - 3,400 mg/kg LD50 Dermal - rabbit - 4,240 mg/kg
	Other information on acute toxicity	LD50 Intraperitoneal - mouse - 544 mg/kg LD50 Intravenous - mouse - 417 mg/kg LD50 Intraperitoneal - rabbit - 323 mg/kg LD50 Intraperitoneal - guinea pig - 1,201 mg/kg LD50 Intraperitoneal - Hamster - 1,401 mg/kg
Toluene	Oral LD50	LD50 Oral - rat - > 5,580 mg/kg
	Inhalation LC50	LC50 Inhalation - rat - 4 h - 12,500 - 28,800 mg/m3
	Dermal LD50	LD50 Dermal - rabbit - 12,196 mg/kg
Pigment Black 33	Oral LD50	LD50 Oral - rat - > 5,000 mg/kg
	Inhalation LC50	No data available
	Dermal LD50	No data available
Ethyl benzene	Oral LD50	No data available
	Inhalation LC50	No data available
	Dermal LD50	LD50 Dermal - rabbit - 15,433 mg/kg

### Skin Corrosion/Irritation

#### Xylene

Draize test, rabbit, skin: 100% Moderate;  
Draize test, rabbit, skin: 500 mg/24H Moderate;

#### Isobutyl Alcohol

Skin - guinea pig - Mild skin irritation

#### Toluene

Skin - rabbit - Skin irritation - 24 h

#### All other

No data available

### Serious Eye Damage/Eye Irritation

#### Xylene

Draize test, rabbit, eye: 87 mg Mild;  
Draize test, rabbit, eye: 5 mg/24H Severe;

#### Isobutyl Alcohol

Eyes - rabbit - Remarks: Moderate eye irritation

#### All other

No data available

### Respiratory Or Skin Sensitization

#### Isobutyl Alcohol

Dermatitis

#### All other

No data available

### **Germ Cell Mutagenicity**

Toluene

Genotoxicity in vitro - rat - Liver  
DNA damage

All other

No data available

### **Carcinogenicity**

IARC: 2B - Group 2B: Possibly carcinogenic to humans (Ethylbenzene)  
3 - Group 3: Not classifiable as to its carcinogenicity to humans (Toluene, Xylene)

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

This product contains a component that is not classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification.

Isobutyl Alcohol

Carcinogenicity - rat - Oral  
Tumorigenic: Equivocal tumorigenic agent by RTECS criteria. Skin and Appendages: Other: Tumors. Leukaemia  
Carcinogenicity - rat - Subcutaneous  
Tumorigenic: Carcinogenic by RTECS criteria. Gastrointestinal: Tumors. Liver: Tumors.

### **Reproductive Toxicity**

Xylene

There is ample evidence that xylene produces embryotoxicity (reduced body weight, retarded ossification, retarded kidney development, increased extra rib) and fetotoxicity in mice and rats, but xylene is not considered teratogenic.

Toluene

Reproductive toxicity - rat - Inhalation  
Paternal Effects: Spermatogenesis (including genetic material, sperm morphology, motility, and count).  
Experiments have shown reproductive toxicity effects in male and female laboratory animals.  
Developmental Toxicity - rat - Oral  
Effects on Embryo or Fetus: Fetotoxicity (except death, e.g., stunted fetus).  
Damage to fetus possible  
Suspected human reproductive toxicant

All other

No data available

### **Specific Target Organ Toxicity Single Exposure**

Isobutyl Alcohol

Inhalation - May cause respiratory irritation.  
May cause drowsiness or dizziness.

All other

No data available

### **Specific Target Organ Toxicity Repeated Or Prolonged Exposure**

All other

No data available

### **Aspiration Hazard**

Aspiration into the lungs can cause fatal chemical pneumonitis.

## Section 12 – Ecological Information

---

### General Comments:

Do not allow material to be released into the environment without proper governmental permits

### Environmental Toxicity:

#### Xylene

Toxicity to fish

Rainbow trout: LC50 = 13.5 mg/L; 96 Hr;  
Unspecified Goldfish: LD50 = 13 mg/L; 24 Hr;  
Unspecified Fathead Minnow: LC50 = 46 mg/L; 1 Hr

Toxicity to daphnia and other aquatic invertebrates

EC50 (48 Hr.) water flea = 3.82 mg/L, flow -through conditions

#### Molybdenum disulfide

Toxicity to fish

LC50 - Pimephales promelas (fathead minnow) – 609 mg Mo/L – 96 h

Toxicity to daphnia and other aquatic invertebrates

EC50 - Daphnia magna (Water flea) - 1680 mg Mo/l - 48 h

#### Isobutyl Alcohol

Toxicity to fish

LC50 - Pimephales promelas (fathead minnow) – 1.220 mg/l - 96 h

Toxicity to daphnia and other aquatic invertebrates

EC50 (48 Hr.) water flea = 1030 mg/L

Toxicity to Microorganisms

EC50 (48 Hr.) Freshwater Algae = 230 mg/L

#### Toluene

Toxicity to fish

LC50 - Lepomis macrochirus (Bluegill) - 74.00 - 340.00 mg/l - 96 h  
LC50 - Oncorhynchus mykiss (rainbow trout) - 7.63 mg/l - 96 h  
NOEC - Pimephales promelas (fathead minnow) - 5.44 mg/l - 7 d  
LOEC - Pimephales promelas (fathead minnow) - 8.04 mg/l - 7 d

Toxicity to daphnia and other aquatic invertebrates

EC50 - Daphnia magna (Water flea) - 8.00 mg/l - 24 h  
Immobilization EC50 - Daphnia magna (Water flea) - 6 mg/l - 48 h

Toxicity to Microorganisms

EC50 - Chlorella vulgaris (Fresh water algae) - 245.00 mg/l - 24 h  
EC50 - Pseudokirchneriella subcapitata (green algae) - 10.00 mg/l - 24 h

#### Pigment Black 33

Toxicity to fish

LC0: > 1,000 mg/l – Golden orfe

Toxicity to daphnia and other aquatic invertebrates

EC0: > 10,000 mg/l - water flea

Toxicity to Microorganisms

Ec0: > 1,000 mg/l – Pseudomonas putida

#### Ethylbenzene

Toxicity to fish

LC50 - Cyprinodon variegatus (sheepshead minnow) - 88.00 mg/l - 96 h  
LC50 - Lepomis macrochirus (Bluegill) - 80.00 mg/l - 96 h  
NOEC - Cyprinodon variegatus (sheepshead minnow) - 88 mg/l - 96 h  
LC50 - Oncorhynchus mykiss (rainbow trout) - 4.2 mg/l - 96 h

Toxicity to daphnia and other aquatic invertebrates

EC50 - Daphnia magna (Water flea) - 2.90 mg/l - 48 h

Toxicity to Microorganisms

Freshwater Algae 1.7 - 7.6 mg/L EC50 96 h  
 2.6 - 11.3 mg/L EC50 72 h  
 4.6 mg/L EC50 = 72 h  
 438 mg/L EC50 > 96 h

**Section 13 – Disposal Considerations**

**Waste Disposal Method:**

**RCRA Hazard Class (40 CFR 261)**

When a decision is made to discard this material, as received, is it classified as a hazardous waste? Yes

Characteristic Waste:

Ignitable: D001

TCLP: D018

State or local laws may impose additional regulatory requirements regarding disposal.

**Contaminated Packaging**

Dispose of as unused product.

**Section 14 – Transportation Information**

**Hazardous for Shipping:** Yes

**Based on 49 CFR, IATA and IMDG:**

**UN Number:** UN1263

**UN Proper Shipping Name:** Paint

**Hazard Class:** 3

**Packing Group:** III

**Labels:** Flammable Liquid

**Placards:** Flammable Liquid

**Section 15 – Regulations**

**TSCA (Toxic Substances Control Act) Regulations, 40 CFR 710:** All hazardous ingredients are on the TSCA Chemical Substance Inventory.

Component	%	CAS Number	SARA 313	SARA 302	New Jersey RTK List	Pennsylvania RTK List	Massachusetts RTK List	California Prop 65 list
Xylene	< 32%	1330-20-7	Yes	Yes	Yes	Yes	Yes	No
Molybdenum disulfide	< 4%	1317-33-5	No	No	Yes	Yes	Yes	No
Dimethyl, diphenyl, methyl, phenyl silicone resin	< 33%	28630-33-3	No	No	Yes	Yes	No	No
Isobutyl Alcohol	< 14%	78-83-1	No	No	Yes	Yes	Yes	No
Toluene	< 12%	108-88-3	Yes	Yes	Yes	Yes	Yes	Yes
Pigment Black 33	< 3%	75864-23-2	Yes	Yes	Yes	No	No	No
Ethyl benzene	< 6%	100-41-4	Yes	No	Yes	Yes	Yes	Yes
Aluminum*	< .03%	7429-90-5			Yes	No	No	No
Magnesium*	< .007%	7439-95-4			Yes	No	No	No
Barium*	< .005%	7440-39-3			Yes	No	No	No



Copper*	< .004%	7440-50-8			Yes	No	No	No
Chromium*	< .003%	7440-47-3			Yes	Yes	Yes	No
Nickel*	< .002%	7440-02-0			No	Yes	Yes	Yes
Arsenic*	< .000002%	7440-38-2			No	No	Yes	No
Cadmium*	< .0000002%	7440-43-9			No	No	Yes	No
Cobalt*	< .0009%	7440-48-4			No	No	No	Yes

\*These are a composite of a pigment and do not exist in a free state. Please note that these were random sample analyses and content may vary from batch to batch.

**SARA 311 / 312 Hazards:** Flammable Hazard ,Acute Health Hazard, Chronic Health Hazard

**Section 16 – Other Information**

---

**Date Prepared:** 06/10/2014

**Date Updated:** 02/07/2017

**Date Printed:** 12/28/2017

This information is furnished without warranty, representation, inducement or license of any kind, except that it is accurate to the best of Tech Line Coatings, Inc., knowledge or obtained from sources believed by Tech Line Coatings, Inc. to be accurate but does not purport to be all inclusive, and Tech Line Coatings, Inc., does not assume any legal responsibility for use or reliance upon same. Before using any chemical, read its label, instructions and safety data sheet.